

MINIATURE VIBRATION MOTOR STRUCTURE

Background of the Invention

1. Field of the Invention

The present invention primarily relates to a miniature vibration motor structure, and more particularly to a miniature vibration motor structure required with a smaller volume.

2. Description of the Related Art

A conventional miniature vibration motor structure in accordance with the prior art shown in Fig. 9 comprises an upper casing 90 and a lower casing 91 secured with each other. The upper casing 90 is provided with a seat 92 protruding upward, and the lower casing 91 is also provided with a seat 92 protruding downward. A bearing 93 is received in the seat 92. A central shaft 94 is pivoted with the upper and lower bearings 93. The central shaft 94 is fitted with a counterweight 95 that is combined with a rotor 96. The outer periphery of the rotor 96 has a permanent magnet 97 induced with a coil seat 98. The counterweight 95 of the rotor 96 is partially recessed to form a recess 99, so that vibration is generated during rotation of the rotor 96.

The conventional miniature vibration motor is usually available in the communication equipment, such as a calling machine, a mobile telephone (or cellular phone) or the like. The design of the communication equipment is required strictly to be light, thin, and small. However, in the construction of such a kind of conventional miniature vibration motor, the upper casing 90 is provided with a seat 92 protruding upward, and the lower casing 91 is also provided with a seat 92 protruding downward for receiving the bearing 93, while the outer side of the central shaft 94 is fitted with a counterweight 95. Thus, the conventional miniature vibration motor has multiple parts, thereby

1 causing inconvenience in assembly, and relatively, the thickness and volume
2 thereof cannot be reduced easily.

3 Summary of the Invention

4 The primary objective of the present invention is to provide a
5 miniature vibration motor structure, wherein the miniature vibration motor has
6 a simpler construction, and has a smaller volume and thickness.

7 In accordance with the present invention, there is provided a
8 miniature vibration motor structure includes a housing having a hole for
9 receiving and positioning one end of a shaft whose other end is positioned in a
10 fixing plate. A rotor includes a bearing integrally combined with an annular
11 permanent magnet. The bearing of the rotor is supported and rotated on the
12 shaft. The bearing or the annular permanent magnet is provided with a recess
13 or protruding block, so that the center of gravity and the center of rotation of
14 the rotor are not in concert with each other. A stator seat is wound with a coil
15 and has a power inlet for supplying an electric power into the stator seat. The
16 stator seat has poles which may be induced with the permanent magnet of the
17 rotor.

18 Further benefits and advantages of the present invention will become
19 apparent after a careful reading of the detailed description with appropriate
20 reference to the accompanying drawings.

21 Brief Description of the Drawings

22 Fig. 1 is an exploded perspective view of a miniature vibration motor
23 structure in accordance with a first embodiment of the present invention;

24 Fig. 2 is a cross-sectional assembly view of the miniature vibration
25 motor structure as shown in Fig. 1;

1 Fig. 3 is a cross-sectional assembly view of a miniature vibration
2 motor structure in accordance with a second embodiment of the present
3 invention;

4 Fig. 4 is a perspective view of a rotor of a miniature vibration motor
5 structure in accordance with a third embodiment of the present invention;

6 Fig. 5 is a perspective view of a rotor of a miniature vibration motor
7 structure in accordance with a fourth embodiment of the present invention;

8 Fig. 6 is a cross-sectional assembly view of the miniature vibration
9 motor structure in accordance with the fourth embodiment of the present
10 invention;

11 Fig. 7 is a cross-sectional assembly view of a miniature vibration
12 motor structure in accordance with the fifth embodiment of the present
13 invention;

14 Fig. 8 is a cross-sectional assembly view of a miniature vibration
15 motor structure in accordance with the sixth embodiment of the present
16 invention; and

17 Fig. 9 is a cross-sectional assembly view of a conventional miniature
18 vibration motor structure in accordance with the prior art.

19 **Detailed Description of the Preferred Embodiments**

20 Referring to the drawings and initially to Fig. 1, a miniature vibration
21 motor structure in accordance with a first embodiment of the present invention
22 comprises a housing 1, a stator seat 2, and a rotor 3.

23 The housing 1 defines a hole 11 for receiving and positioning one
24 end of a shaft 12 whose other end may be positioned in the base plate of a
25 conventional communication equipment. The shaft 12 is fitted in the shaft hole
26 33 of the rotor 3, for supporting the rotor 3 to rotate in a positioning manner. A
27 positioning ring 13 is rested on the rotor 3. The housing 1 has a periphery

FIG. 2

1 provided with protruding locking blocks 14, so that the housing 1 may be fixed
2 on a fixing plate such as a circuit board or a base plate.

3 The stator seat 2 is wound with a coil 21, and has a power inlet 22 for
4 supplying the electric power into the stator seat 2. The stator seat 2 has poles 23
5 which may be induced with the permanent magnet 32 of the rotor 3, to drive
6 the rotor 3 to rotate.

7 The rotor 3 includes a bearing 31, and an annular permanent magnet
8 32 integrally formed on the outer periphery of the bearing 31. The center of the
9 rotor 3 has a shaft hole 33 for passage of the shaft 12, so that the rotor 3 is
10 supported by the shaft 12 to rotate. The permanent magnet 32 of the rotor 3 is
11 induced with the poles 23 of the stator seat 2, so that the rotor 3 can be driven to
12 rotate. In the preferred embodiment, the annular permanent magnet 32 on the
13 periphery of the rotor 3 is provided with a protruding block 34, so that the
14 center of gravity and the center of rotation of the rotor 3 are not at the same
15 central line. Thus, the rotation of the rotor 3 will form an unbalanced vibration.

16 Referring to Fig. 2, the miniature vibration motor structure in
17 accordance with the first embodiment of the present invention is assembled.
18 The housing 1 is fixed on a fixing plate 4 such as a circuit board or a base plate.
19 The locking blocks 14 of the housing 1 may be bent so that the housing 1 is
20 fixed on the fixing plate 4. The two ends of the shaft 12 are respectively
21 positioned in the hole 11 of the housing 1 and the fixing plate 4. The shaft 12 is
22 passed through the shaft hole 33 of the rotor 3, for supporting the rotor 3 to
23 rotate. Thus, when the permanent magnet 32 of the rotor 3 is induced with the
24 poles 23 of the stator seat 2, the rotor 3 can be driven to rotate. In addition, the
25 rotor 3 is provided with the protruding block (34) so that the center of gravity
26 and the center of rotation of the rotor 3 are not at the same central line. Thus,
27 the rotation of the rotor 3 will form an unbalanced vibration.

Patented September 2, 1959

1 Referring to Fig. 3, in accordance with a second embodiment of the
2 present invention, the annular permanent magnet 32 on the periphery of the
3 rotor 3 is provided with a recess 35, so that the center of gravity and the center
4 of rotation of the rotor 3 are not at the same central line. Thus, the rotation of
5 the rotor 3 will form an unbalanced vibration.

6 Referring to Fig. 4, in accordance with a third embodiment of the
7 present invention, the recess 35 defined in the annular permanent magnet 32 on
8 the periphery of the rotor 3 is embedded with an insert 36 having different
9 material and specific gravity, so that the center of gravity and the center of
10 rotation of the rotor 3 are not at the same central line. Thus, the rotation of the
11 rotor 3 will form an unbalanced vibration.

12 Referring to Figs. 5 and 6, in accordance with a fourth embodiment
13 of the present invention, the bearing 31 of the rotor 3 is provided with a recess
14 37, so that the center of gravity and the center of rotation of the rotor 3 are not
15 at the same central line. Thus, the rotation of the rotor 3 forms an unbalanced
16 vibration.

17 Referring to Fig. 7, in accordance with a fifth embodiment of the
18 present invention, the recess 37 defined in the bearing 31 of the rotor 3 is
19 embedded with an insert 38 having different material and specific gravity, so
20 that the center of gravity and the center of rotation of the rotor 3 are not at the
21 same central line. Thus, the rotation of the rotor 3 will form an unbalanced
22 vibration.

23 Referring to Fig. 8, in accordance with a sixth embodiment of the
24 present invention, the bearing 31 of the rotor 3 is provided with a protruding
25 block 39, so that the center of gravity and the center of rotation of the rotor 3
26 are not at the same central line. Thus, the rotation of the rotor 3 will form an
27 unbalanced vibration.

104490-1-10

1 Accordingly, in the miniature vibration motor structure in
2 accordance with the present invention, the bearing and the rotor are integrally
3 combined with each other. In addition, the bearing or the annular permanent
4 magnet of the rotor may be provided with a protruding block, a recess or an
5 insert, so that the center of gravity and the center of rotation of the rotor are not
6 at the same central line. Thus, the rotation of the rotor will form an unbalanced
7 vibration. Therefore, the entire construction of the vibration motor structure in
8 accordance with the present invention is simple, and the volume and weight
9 thereof may be largely shortened and reduced. Thus, the vibration motor of the
10 present invention may satisfy the light, thin and small requirements of the
11 communication equipment.

12 Although the invention has been explained in relation to its preferred
13 embodiment as mentioned above, it is to be understood that many other
14 possible modifications and variations can be made without departing from the
15 scope of the present invention. It is, therefore, contemplated that the appended
16 claim or claims will cover such modifications and variations that fall within the
17 true scope of the invention.